


ARA58-F-EN-V2



ARA58-F-EN-V2



ARA58-F-AUX-V2

- Simple installation.
- Supports GSM/WCDMA/LTE-FDD/LTE-TDD.
- Supports connecting the platform through wireless network.
- Used with Emergency Phone Tower.

Technical Specification

Port

Network Mode

ARA58-F-EN-V2: GSM: 900/1800MHz, WCDMA: B1/B5/B8, LTE-FDD: B1/B3/B5/B7/B8/B20, LTE-TDD: B38/B40/B41
 ARA58-F-AUX-V2: GSM: 850/900/1800/1900MHz, WCDMA: B1/B2/B5/B8, LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B28, LTE-TDD: B40

General

Power Consumption	4 W
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	10%–90% (RH)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging Dimensions	83 mm × 58 mm × 258 mm (3.27" × 2.28" × 10.16"); 83 mm × 58 mm × 260 mm (3.27" × 2.28" × 10.24")
Net Weight	< 90 g (0.20 lb)

Dimensions (mm/inch)

