

Smoke detector

SD119-2L



Product Features:

- 2 wire model
- Advanced detection and discrimination algorithms
- Easy installation and maintenance
- Sleek low-profile housing design
- Durable sensor head, no need for replacement

- SMD circuit board design-satisfactory quality and reliability guaranteed
- Integrated heat detector for SD 119-2H model
- N/C (normal/close)-N/O (normal/open)selectable relay output
- AR (Auto Reset) function for security systems (optional for 4 wire models) Sensor base option: standard and Shottky Diode

The range includes:

SD-119-2L 2 wire photoelectric smoke alarm with remote LED output

Model	2/4 wire	Heat Sensor Setting	Voltage DC (Min./Max.)	Standby Current (Max.)	Alarm Current (12/24V)	Surge Current (Max.)	Start-Up Time (Max.)	Permissible Current (Max.)	Cycle Time	Alarm contact	Certified	Base Model No.
SD119-2L	2		10.8~33V	80μA	22/55mA	160μA	30 Sec.	80mA	1-3 Sec.	Remote LED	UL/EN	P/N852001

Specification:

Smoke Sensitivity	0.98--2.40%/FT Obscuration (UL) ; 0.08--0.14 dB/m (EN)
Ceiling Spacing	50 foot rating for heat sensor
Temperature Range	-10°C to 50°C
Humidity	0 to 95% RH, no condensation or icing
Dimensions	100mm (dia.) x 46mm (ht) with base
Weight	130g/set with base