

TV-SATELLITAL TAPS 2.4GHZ

The bdn Taps are designed to comply with the highest current standards for Analog and Digital TV/SAT technologies. BDN taps are manufactured with a shielded zamak chassis for greater protection from electromagnetic interference, ideal for community TV projects, television networks in hotels, hospitals and shopping centers.

TECH SPECIFICATION

Description	INDOOR 2.4GHz TAP 4-WAY				
Item	Tap Value	12	20	24	27
Tap loss (IN-TAP)	±1.5dB				±1.5dB
Insertion Loss (IN-OUT)	-dB Max				
5-47MHz	4,5	2	1,5	1,2	
47-1000MHz	4,5	2	1,5	1,2	
1000-1750MHz	5,5	3	2,5	2,4	
1750-2150MHz	5,5	3	2,5	2,4	
2150-2400MHz	6	3,5	3	2,8	
Insolation (TAP-TAP)	-dB Min				
5-47MHz	20	20	20	20	
47-1000MHz	20	20	20	20	
1000-1750MHz	20	20	20	20	
1750-2150MHz	20	20	20	20	
2150-2400MHz	20	20	20	20	
Insolation (TAP-OUT)	-dB Min				
5-47MHz	22	22	22	22	
47-1000MHz	22	22	22	22	
1000-1750MHz	22	22	22	22	
1750-2150MHz	22	22	22	22	
2150-2400MHz	22	22	22	22	
Return Loss (IN, OUT, TAP)	-dB Min				
5-47MHz	15	15	15	15	
47-1000MHz	15	15	15	15	
1000-1750MHz	15	15	15	15	
1750-2150MHz	15	15	15	15	
2150-2400MHz	15	15	15	15	
DC PASS	IN <- -> OUT 24V 500mA				