

DIGITAL TAPS 1.2GHZ

The bdn Taps are designed to comply with the highest current standards of the SCTE (Society of Cable Telecommunications Engineers). They support bidirectional digital data and multimedia communications over Docsis 3.1 QPSK and QAM protocol, in addition to integrating 6kv surge protection.

TECH SPECIFICATION

Description									
Tap Value	8	11	14	17	20	23	24	27	30
Item	GM	GM	GM	GM	GM	GM	GM	GM	GM
Insertion Loss (IN-OUT)									
5-40MHz		≤3.5	≤2.6	≤1.5	≤1.0	≤1.0	≤1.0	≤1.0	≤1.0
41-470MHz		≤3.5	≤2.6	≤1.5	≤1.0	≤1.0	≤1.0	≤1.0	≤1.0
471-550MHz		≤3.8	≤3.0	≤1.8	≤1.2	≤1.0	≤1.0	≤1.0	≤1.0
551-750MHz		≤3.8	≤3.0	≤1.8	≤1.2	≤1.2	≤1.2	≤1.2	≤1.2
751-860MHz		≤4.0	≤3.4	≤2.2	≤1.5	≤1.2	≤1.2	≤1.2	≤1.2
861-950MHz		≤4.0	≤3.4	≤2.2	≤1.5	≤1.2	≤1.2	≤1.2	≤1.2
950-1218MHz		≤4.3	≤3.5	≤2.5	≤1.7	≤1.6	≤1.4	≤1.4	≤1.4
Tap Loss (IN-TAP)	±1.5								
5-1218MHz	8	11	14	17	20	23	24	27	30
Isolation (TAP-TAP)									
5-40MHz	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
41-470MHz	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
471-550MHz	≥23	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
551-750MHz	≥22	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
751-860MHz	≥22	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
861-950MHz	≥22	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25
950-1218MHz	≥22	≥25	≥25	≥25	≥25	≥25	≥25	≥25	≥25

DIGITAL TAPS 1.2GHZ

Isolatio (TAP-OUT)										
5-40MHz	≥26	≥28	≥30	≥32	≥34	≥38	≥38	≥40	≥42	
41-470MHz	≥28	≥30	≥30	≥30	≥30	≥38	≥40	≥42	≥42	
471-550MHz	≥26	≥28	≥30	≥30	≥30	≥36	≥38	≥42	≥40	
551-750MHz	≥25	≥24	≥26	≥26	≥26	≥32	≥34	≥38	≥40	
751-860MHz	≥25	≥24	≥26	≥26	≥26	≥32	≥34	≥38	≥38	
861-950MHz	≥25	≥24	≥24	≥25	≥25	≥30	≥32	≥36	≥38	
950-1218MHz	≥25	≥24	≥24	≥25	≥25	≥30	≥32	≥36	≥38	
ReturnLoss (IN,OUT,TAP)										
5-40MHz	18	18	18	18	18	18	18	18	18	
41-470MHz	18	18	18	18	18	18	18	18	18	
471-550MHz	18	18	18	18	18	18	18	18	18	
551-750MHz	18	18	18	18	18	18	18	18	18	
751-860MHz	18	18	18	18	18	18	18	18	18	
861-950MHz	18	18	18	18	18	18	18	18	18	
950-1218MHz	18	18	18	18	18	18	18	18	18	
Impedance	75 Ohms				Test Enviroment Temperature		+25°C			
RFI Shielding	-110 dB									
Intermodulation	-100 dB									